



Hikvision 4 MP Bullet IP Security Camera

Product Specification

Brand	Hikvision
Model	DS-2CD3047G0E-LUF
Type	IP Bullet Camera
Interface	4 MP ColorVu Fixed Bullet Network Camera With In-build Audio
Camera	Image Sensor : 1/2.7" Progressive Scan CMOS Min. Illumination : Color: 0.001 Lux @ (F1.0, AGC ON) Shutter Speed : 1/3 s to 1/100,000 s Angle Adjustment : Pan: 0° to 360°, tilt: 0° to 90°, rotate: 0° to 360° Slow Shutter P/Women Wide Dynamic : Range 120 dB.
Lens	Lens Type & FOV : 2.8 mm, horizontal FOV 97°, vertical FOV 51°, diagonal FOV 114° 4 mm, horizontal FOV 76°, vertical FOV 41°, diagonal FOV 89° 6 mm, horizontal FOV 50°, vertical FOV 27°, diagonal FOV 58° Aperture : F1.0 Lens Mount : M12 Aperture Type : Fixed Depth of Focus : 2.8 mm: 3.1 m to 4 mm: 3.6 m to 6 mm: 7.8 m to
Illumination	Smart Supplement Light Supplement Light White White Light Range Up to 30 m
Video	Max. Resolution : 2560 × 1440 Main Stream : 50Hz: 20 fps (2560 × 1440) 25 fps (2304 × 1296, 1920 × 1080, 1280 × 720) 60Hz: 20 fps (2560 × 1440) 30 fps (2304 × 1296, 1920 × 1080, 1280 × 720) Sub Stream : 50Hz: 25 fps (640 × 480, 640 × 360, 320 × 240) 60Hz: 30 fps (640 × 480, 640 × 360, 320 × 240) Third Stream : 50Hz: 1 fps (640 × 360) 60Hz: 1 fps (640 × 360)
Audio	Environment Noise Filtering -U: Yes Audio Sampling Rate -U: 8 kHz/16 kHz Audio Compression -U: G.711ulaw/G.711alaw/G.722.1/G.726/MP2L2/PCM/AAC