



Zebra LI4278 Cordless Barcode Scanner

Product Specification

Brand	ZEBRA
Model	LI4278
Type	Handheld Scanner
Tolerance	Skew Tolerance : $\pm 65^\circ$ Pitch Tolerance : $\pm 65^\circ$ Roll Tolerance : $\pm 45^\circ$ Motion Tolerance : 25 in./ 63.5 cm per second
Scan Pattern	Single bright aiming line
Scan Angle	Horizontal 35°
Scan Speed	547 scans per second
Light Source	LED Class 1 device 617nm (amber)
Print Contrast	Min.15% MRD
Scans Per Charge	Up to 57,000
Operation Temperature	32° F to 122° F/ 0° C to 50°C
Storage Temp	-40° F to 158° F/-40° C to 70° C
Supported Humidity	5% to 85% RH, non-condensing

Decode Range	3 mil : Minimum resolution 4 mil : 4-10 in./10.2-25.4 cm 5 mil : 3-13 in./7.6-33 cm 7.5 mil : 1.5-19 in./ 3.8-48.3 cm 13 mil (100% UPC-A) : 1-31 in./2.5-78.7 cm 20 mil : 1-42 in./2.5-106.7 cm 26 mil (200% UPC-A) : 3-55 in./7.6-140 cm
--------------	---