



Hikvision DS-7108NI-Q1/M 8-ch Mini 1U NVR

Product Specification

Brand	Hikvision
Model	DS-7108NI-Q1/M
Type	8-ch Mini 1U NVR
IP Video Input	8-ch
Incoming Bandwidth	60 Mbps
Outgoing Bandwidth	60 Mbps
HDMI Output	1-ch 1920 × 1080p/60Hz 1280 × 1024/60Hz 1280 × 720/60Hz 1024 × 768/60Hz
VGA Output	1-ch 1920 × 1080p/60Hz 1280 × 1024/60Hz 1280 × 720/60Hz 1024 × 768/60Hz
Decoding Format	H.265+/H.265/ H.264+/H.264
Recording Resolution	4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
Decoding Capability	4-ch@1080p (25 fps), 2-ch@4 MP (25 fps)
Network Protocol	TCP/IP DHCP Hik-Connect DNS DDNS NTP SADP SMTP UPnP
Network interface	1, RJ-45 10/100Mbps self-adaptive Ethernet interface
SATA Ports	1 SATA interfaces
USB Interface	Rear Panel: 2 × USB 2.0
Working temperature	-10 to +55° C (+14 to +131° F)

Humidity	10% to 90%
Power Supply	12 VDC, 1.5 A
Power Consumption	≤ 10 W